

HHR Configuration for Magellan 2xxx / 8xxx / 9xxx AUX-Port

HHR Konfiguration für Magellan 2xxx / 8xxx / 9xxx AUX-Port

Cable: CAB-362 SH3924 (90G001092)

Restore Default



\$+\$*

RS232 – 9600/8/N/1 – RTS/CTS



\$+CPOCE1\$-

Inter-Character Delay



\$+CKO2\$-

Disable Terminator



\$+EA10\$-

Enable Custom Code Identifier



\$+EB3\$-

Set Code Identifier UPC-A “A”



\$+EHC41FF\$-

Set Code Identifier UPC-E “E”



\$+EHD45FF\$-

Set Code Identifier EAN-13 “F”



\$+EHB46FF\$-

Set Code Identifier EAN-8 “FF”



\$+EHA4646\$-

Optional: CODE 128, CODE 39, CODE 93, INTERLEAVED 2/5, PDF 417

Set Code Identifier CODE 128 “#”



Set Code Identifier CODE 39 “*”**



CODE 39 append trailing *



Set Code Identifier CODE 93 “&”



Set Code Identifier INTERLEAVED 2/5 “i”



Set Code Identifier PDF 417 “P”



Optional: Enable Code EAN 128 & Set Code Identifier EAN-128 “[C1”



Optional: Enable RSS Codes & Set Code Identifier "R4"

Enable **RSS Expanded Linear and Stacked** & Set Code Identifier "R4"



Enable **RSS Limited** & Set Code Identifier "R4"



Enable **RSS 14 Linear and Stacked** & Set Code Identifier "R4"



2xxx / 8xxx / 9xxx Handheld Port Enable
(Please read this with the Magellan!)
(Bitte dies mit dem Magellan lesen!)

Enable HandHeld Port

