



SELF TEST PROGRAMMING

FOR EPSON TM-T88V WITH INBUILD
USB PORT AND ADDITIONAL SERIAL PORT INTERFACE

INTERFACE SELECTION CHANGE
FROM UIB OR BUILT-IN USB
TO AUTOMATIC DETECTION

INSTRUCTIONS:

- SWITCH OFF THE PRINTER
- PRESS FEED BUTTON WHILE PRINTER IS SWITCHED ON (~5 SEC)
- RELEASE FEED BUTTON WHEN PRINT OUT STARTS
- PRESS **1 TIME** > **1 SECOND** THE FEED BUTTON
- PRESS **3 TIMES** < **1 SECOND** THE FEED BUTTON
- PRESS **1 TIME** > **1 SECOND** THE FEED BUTTON
- PRESS **10 TIMES** < **1 SECOND** THE FEED BUTTON
- PRESS **1 TIME** > **1 SECOND** THE FEED BUTTON
- PRESS **3 TIMES** < **1 SECOND** THE FEED BUTTON
- PRESS **1 TIME** > **1 SECOND** THE FEED BUTTON
- TURN OFF THE PRINTER

CROSS CHECK:

- PRESS FEED BUTTON WHILE PRINTER IS SWITCHED ON (~5 SEC)
- RELEASE FEED BUTTON WHEN PRINT OUT STARTS
- CHECK THE SECOND LINE ON TOP:

RESULT MUST BE: → **” USB or Serial Interface ”**