

# POS thermal printer

## BTP-S80 POS thermal printer



### Features:

- High speed printing , up to 250mm/s
- Compact design reduces space occupancy up to 40%-50%, meet the small space application
- Supports top paper out and front paper out application
- Supports wall mounting, can also used as panel printer or kiosk printer without shell
- Easy to open with one hand, can effectively protect the front cover
- Paper near end sensor adjustable
- Supports 6 adjustable mark sensor position to meet variety application of black mark paper



### Applications:

- Retail
- Finance
- Catering
- Entertainment
- Health care
- Logistic

## > BTP-S80 POS thermal printer

Item		BTP-S80
Print	Print method	Direct thermal
	Resolution	203x203DPI
	Print width	80mm(Max.)
	Print speed	Max 250mm/s
	Memory	RAM 2MB, FLASH 4MB
	Sensor	Paper near end sensor, Paper end sensor, TPH position
	Driver	Windows drivers(Win2000/XP/2003/VISTA/2008/Win7/Win8/Win10); Linux CUPS, MAC
	Interface	Standard interface: USB2.0(On-board); Optional interface: Serial(RS-232), Parallel(IEEE1284), Ethernet, WLAN(Wi-Fi), Bluetooth, Ethernet+Serial(RS-232)
Cash drawer control	1~2 cash drawers	
Barcode Fonts Graphics	Barcode	1D:UPC-A,UPC-E ,JAN8 (EAN8),JAN13 (EAN13), CODE 39,CODE 93 CODE 128, ITF,CODABAR 2D:PDF417,QR,Maxicode, GS1-DataBar
	Font	Font A (12 x 24);Font B (9 x 17 ),traditional Chinese, Korean, Japanese, Thai, Kanji font A: 24x24, Simplified Chinese(GB23121, GB18030), English, HK
	Character set	95 Alphanumeric, 14 types International characters, 128x57 Graphic (including user-defined page),Traditional/Simplified Chinese, Thai, Japanese, Korean (optional)
	Character modification	Rotate (0°, 90°, 180°, 270°), emphasize, underline, reverse, enlarge(1-6X)
Paper	Graphics printing	Bitmap image downloading and direct bitmap image print, RAM bitmap download: buffer size 128KB, FLASH bitmap download: buffer size 512KB
	Paper type	Continuous paper, Marked paper
	Paper thickness	0.06mm~0.1mm
	Paper width	82.5 ± 0.5mm, 80 ± 0.5mm, 76 ± 0.5mm, 69 ± 0.5mm, 57.5 ± 0.5mm
	Paper roll OD	83mm (Max.)
Power supply	Paper cut	Full cut, Partial cut
	Input	100~240V AC, 50~60Hz
Reliability	Output	24V ± 5%DC, coverage current 2A
	Print head lifetime	150Km
Environment	Cutter lifetime	2,000,000 cuts
	Operation condition	5°C to 45°C, 20% to 90%RH (40°C)
Physics Spec.	Storage condition	-40°C to 60°C, 20% to 93%RH (40°C)
	Dimensions	127mm(L) x 127mm(W) x 134mm(H)
Standards	Weight	Approx.1.3Kg
	Standards	CE, CB, UL, FCC, CCC



Shandong New Beiyang Information Technology Co., Ltd  
No.126 Kuntun Rd, Huancui Zone, Weihai, Shandong, China 264203  
Phone: +86(0)631 567 3777 Fax: +86(0)631 567 3778  
E-mail: sales@newbeiyang.com  
www.newbeiyang.com

\* All photos are for reference only, the appearance will be subject to physical product functions and parameters are subject to change without prior notice